

TECHNICAL DATA

Fluke Calibration 9102S Handheld Dry-Well



Key features

- Temperature ranges from -10°C to 375°C .
- Accuracy to $\pm 0.25^{\circ}\text{C}$, with stability of $\pm 0.05^{\circ}\text{C}$ at 0°C .
- Equipped with an RS-232 interface for connectivity.

Product overview: Fluke Calibration 9102S Handheld Dry-Well

9102S Dry-Well

For work in the temperature range of -10°C to 122°C , 9102S dry-well is another first in the industry, featuring stability to $\pm 0.05^{\circ}\text{C}$.

This dry-well is only four inches high and six inches wide, achieves temperatures as low as -10°C , includes a NIST-traceable calibration, and is stable to $\pm 0.05^{\circ}\text{C}$. The Model 9102S is excellent for dial gauges, digital thermometers, bulb switches, and other sensors that need calibration below ambient.

The 9102S has two wells so you can use one for a reference thermometer to increase accuracy. Both wells are 1/2 inch in diameter, and each has inserts available for almost any sensor size.

Specifications: Fluke Calibration 9102S Handheld Dry-Well

Ordering information



Fluke 9102S-156

9102S-156, DRY-WELL, HH LOW-TEMP

9102S

HDRC Handheld Dry-Well

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2025 Fluke Corporation.
Specifications subject to change without notice.
06/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**